



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) **EP 1 087 339 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
28.03.2001 Bulletin 2001/13

(51) Int. Cl.<sup>7</sup>: **G06T 11/00**

(21) Application number: 00308209.6

(22) Date of filing: 20.09.2000

(84) Designated Contracting States:  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE  
Designated Extension States:  
AL LT LV MK RO SI

(30) Priority: 24.09.1999 FR 9911960

(71) Applicant: GE MEDICAL SYSTEMS SA  
78533 Buc Cedex (FR)

(72) Inventors:  
• Vaillant, Régis  
91140 Villebon sur Yvette (FR)

• Launay, Laurent  
78470 St. Remy, Les Chevreuse (FR)  
• Lienard, Jean  
92140 Clamart (FR)  
• Sureda, Francisco  
92290 Chatenay Malabry (FR)

(74) Representative:  
Pedder, James Cuthbert  
GE London Patent Operation,  
Essex House,  
12/13 Essex Street  
London WC2R 3AA (GB)

(54) **Method of reconstruction of a three-dimensional image of an element of interest**

(57) A method of reconstruction of a three-dimensional image of an element of interest comprises a phase of acquisition of digital radiographic images by rotation of an camera around the organ, a phase of marking the position of the element of interest from image to image, and a phase of reconstruction of the three-dimensional image of the element of interest from acquired images and positions of the element of interest successively located in the successive images.

EP 1 087 339 A1

## Description

[0001] The invention concerns the reconstruction of three-dimensional images and, in particular, the reconstruction of a three-dimensional image of an element of interest like, for example, a vascular stent inserted in an organ such as a vessel.

[0002] The invention is applicable advantageously but not limitatively to the medical field.

[0003] Vascular expanders ("stents") are placed in coronary arteries to eliminate stenosis of those arteries. A major difficulty resides in control of the correct deployment of the stent in the vessel in order to avoid a problem known as restenosis. At present, in order to check correct deployment, that is, in general, the diameter of the stent in the vessel, ultrasound-based intravascular techniques are used, which require the insertion of an extra catheter, carrying an ultrasound probe and therefore relatively expensive.

[0004] The invention is aimed at offering a more satisfactory solution to that problem and proposes furnishing the same information, but from a reconstruction of the three-dimensional image of the stent.

[0005] The invention therefore proposes a method of reconstruction of a three-dimensional image of an element of interest like, for example, a vascular stent inserted in an organ such as a vessel, comprising a phase of acquisition of digital radiographic images by rotation of a camera around the organ, a phase of marking the position of the element of interest from image to image, phase of marking the position of the element of interest from image to image, and a phase of reconstruction of the three-dimensional image of the element of interest from acquired images and positions of the element of interest successively located in the successive images.

[0006] The invention will now be described in greater detail, by way of example:-

[0007] A first phase consists of acquiring a number of digital radiographic images by rotation of a camera of standard structure known per se around a patient, for example, around the patient's chest, if the three-dimensional reconstruction of the image of a vascular stent placed in a coronary artery is of interest. A number of 10 acquisitions per cardiac cycle for about 10 cycles is a nonlimitative example.

[0008] In practice, taking into account the relatively contrasted character of the vascular stent, it does not appear indispensable to undertake in advance the injection of a contrast medium into the vascular system.

[0009] A marking of the position of the element of interest from image to image is then undertaken, preferably in real time. Thus, it is possible to predict the position of the stent from one image to the next. In addition, collimation means can be adjusted to limit the X-ray dose delivered to the patient. By way of indication, it is possible to use as image to image marketing technique ("matching") as described by R. Deriche and O.

Fangeras entitled "Tracking Line segments," *Image and Vision Computing*, Vol. 8, No. 4, November 1990, pages 261-270. The expert may possibly refer to it.

[0010] A phase of reconstruction of the three-dimensional image of the element of interest is then carried out. In that connection, two variants are possible.

[0011] The first consists of describing the three-dimensional image by a regular grid of elementary volume elements commonly designated by the term "voxel" by the expert. The intensities attributed to each voxel then indicate the probability of the voxel being situated or not in the stent.

[0012] Reconstruction of the three-dimensional image can be carried out by means of a standard algebraic iterative algorithm of image reconstruction.

[0013] The principle of such algebraic iterative algorithm of image reconstruction is perfectly known by the expert and has previously been the subject of numerous articles, e.g., Gordon, Bender and Herman entitled "Algebraic reconstruction technique for tridimensional electron microscopy and X-ray photography," *Journal of Theol. Biol.* 29, pages 9471 to 781 (1970), and also French Patent Applications Nos. 89 03606 or 89 16906.

[0014] The method of reconstruction of a three-dimensional image of an object, such as described in French Patent Application No. 2,752,975, can also be used.

[0015] The expert may refer to those documents of the prior art for more information concerning use of the image reconstruction algorithm and/or the camera calibration phase.

[0016] After that reconstruction, one can also envisage carrying out a segmentation phase on the reconstructed three-dimensional image in order to filter out its noise and retain solely the useful representation of the stent. In that connection, the expert may, for example, use an algorithmic technique of segmentation such as that described G. Finet and J. Liénard entitled "Parameters that influence accuracy and precision of quantitative coronary arteriography," *The International Journal of Cardiac Imaging*, Vol. 12, No. 4, Dec. 1996, pages 271-287.

[0017] One can also envisage reconstructing the three-dimensional image of the stent by selecting only the images corresponding to a precise instant of the cardiac cycle. In that regard, a physiological signal such as an electrocardiogram can be used to make the selection of those images.

[0018] In a second variant, reconstruction of the three-dimensional image can be made by describing the stent by means of a parametric model (typically, the length, shape and size of the cross section, the spatial position and the orientation, etc.). Those parameters are then optimized by applying a gradient descent algorithm known per se. The energy to be minimized by the gradient descent algorithm can be a function of the difference between the image really acquired and the image which would be obtained with a given choice of

values of parameters of the stent model.

[0019] This second variant offers the advantage of directly reconstructing a segmented three-dimensional image of the stent.

[0020] Furthermore, in all cases, it may be preferable to apply a movement compensation algorithm in order to compensate for the wide movements of the stent due, for example, to the patient's respiration.

[0021] From a material standpoint, beside the standard camera equipment, a computer is provided, equipped with a screen and incorporating the different software of the invention, notably, matching, segmentation and reconstruction algorithms.

#### Claims

1. Method of reconstruction of a three-dimensional image of an element of interest inserted in an object, comprising the steps of a phase of acquisition of digital radiographic images by rotation of an camera around the object, a phase of marking the position of the element of interest from image to image, and a phase of reconstruction of the three-dimensional image of the element of interest from acquired images and positions of the element of interest successively located in the successive images.
2. Method according to claim 1, wherein the reconstruction phase embraces a representation of the three-dimensional image from a grid of elementary volume elements and use of an iterative algebraic algorithm of image reconstruction.
3. Method according to claims 1 or 2, wherein a parametric model of the element of interest is used.

40

45

50

55



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 00 30 8209

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.CI.7)
X	WO 99 13432 A (UNIV IOWA RES FOUND) 18 March 1999 (1999-03-18) * claim 1 * * page 24, line 15 - line 20 *	1,3	G06T11/00
Y	US 5 724 978 A (TENHOFF HARM) 10 March 1998 (1998-03-10) * abstract; claim 1 *	1-3	
Y	PELLOT C ET AL: "AN ATTEMPT TO 3D RECONSTRUCT VESSEL MORPHOLOGY FROM X-RAY PROJECTIONS AND INTRAVASCULAR ULTRASOUNDS MODELING AND FUSION" COMPUTERIZED MEDICAL IMAGING AND GRAPHICS,US,PERGAMON PRESS, NEW YORK, NY, vol. 20, no. 3, May 1996 (1996-05), pages 141-151, XP002914808 ISSN: 0895-6111 * abstract *	1-3	
A	EP 0 860 144 A (PICKER INT INC) 26 August 1998 (1998-08-26) * claims 1,2 *	1-3	TECHNICAL FIELDS SEARCHED (Int.CI.7) G06T
A	PRAUSE G P M ET AL: "GEOMETRICALLY CORRECT 3-D RECONSTRUCTION OF CORONARY WALL AND PLAQUE: COMBINING BIPLANE ANGIOGRAPHY AND INTRAVASCULAR ULTRASOUND" COMPUTERS IN CARDIOLOGY,US,NEW YORK, IEEE, 1996, pages 325-328, XP000687768 ISBN: 0-7803-3711-5		
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 11 January 2001	Examiner Perez Molina, E
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category A: technological background O: non-written disclosure P: intermediate document</p> <p>T: theory or principle underlying the invention E: earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons A: member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/02 (P04/C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 30 8209

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

11-01-2001

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9913432 A	18-03-1999	US 6148095 A AU 8924198 A	14-11-2000 29-03-1999
US 5724978 A	10-03-1998	EP 0934023 A WO 9811823 A US 5830145 A	11-08-1999 26-03-1998 03-11-1998
EP 0860144 A	26-08-1998	US 5841830 A JP 10243943 A	24-11-1998 14-09-1998

EPO FORM P0488

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82